PRODUCTS OFFER

RANGE OF ACCESSORIES		Fluids	Materials (body/seal)	Maximum operating pressure (bar)	Temperature		PAGE
					Min.	Max.	
ADAPTERS		Compressed air	Brass	200	-40°C	+150°C	294
		Compressed air and industrial water	Nickel-plated brass	60	-10°C	+80°C	298
		Compressed air and industrial water	Stainless steel	200	-20°C	+180°C	301
PLUGS		Compressed air	Brass	200	-60°C	+180°C	304
		Compressed air and industrial water	Nickel-plated brass				306
		Compressed air and industrial water	Steel				306
MANIFOLDS		Compressed air	Brass	20	-10°C	+80°C	308
		Compressed air	Aluminium				309
ACCESSORIES RANGE	for the fittings 	Compressed air	The specifications of the accessories are linked to each range.				310
	for the couplers 	Compressed air and industrial water					311
	for the tubes 	Compressed air					312
	for the valves 	Compressed air and industrial water					316
BLOWGUNS	Premium 	Compressed air	Technical polymer/NBR/ nickel-plated brass	10	-20°C	+80°C	318
	energy-saving 		Technical polymer/NBR/ nickel-plated brass	10	-20°C	+80°C	320
	Safety 		Technical polymer/NBR/ nickel-plated brass	10	-20°C	+80°C	321
	Standard 		Technical polymer/NBR/ aluminium	10	-20°C	+80°C	323
WATER PISTOLS AND WORKSHOP BLOWGUNS		Industrial water oils and lubricants	Treated zamak, nickel-plated brass/NBR	20	-20°C	+100°C	324



WHAT TYPE OF FLUID DO YOU WISH TO CONVEY?

Parker offers ranges dedicated to **compressed air and neutral gases.**

Parker presents ranges specifically designed for **water**, including:

- *Industrial water (tap water)*
- *Treated water (deionised, pure and demineralised)*

All our solutions are compatible with glycol mixtures.

Parker offers ranges for **oils and lubricants.**

LEGRIS RECTUS ADAPTERS



Legris Rectus adapters effectively complement installations equipped with Legris fittings and Rectus couplers, in standard, aggressive or corrosive environments. With a wide range of shapes, they allow for a variety of connection configurations.

Technical specifications

	Materials:	Brass	Nickel-plated brass	Stainless steel
	Fluids:	Compressed air	Compressed air	Air/industrial water and treated water
	Operating pressure:	200 bar	60 bar	200 bar
	Operating temperature:	-40°C to +150°C	-10°C to +80°C	- 40°C to +180°C
	Connection:	G1/8 to G3/4 R1/8 to R1 ¼ NPTF 1/8 to NPTF 3/4	M5x0.8 R1/8 to R ½	G1/8 to G1 R1/8 to R1 ¼ NPT to ½ NPT

Performance depends on the fluids, materials and tube used.

Benefits

- **Wide range of products:** thanks to the wide choice of adapter configurations, users are sure to find the right product for their specific needs, whether for connections, transitions or adaptations.
- **Robustness:** Legris Rectus adapters are manufactured from **high-quality** forged materials, guaranteeing excellent mechanical strength and corrosion resistance.